

Remco Renaissance Rotisserie

Technical Specifications



MODEL DP-36

CAPACITY 36 CHICKENS
25,000 BTU MAIN RADIANTS
5-10,000 BTU INPUT FLICKER FLAME
115 VOLT, 20AMP DEDICATED OUTLET
FULL LOAD 5.7 AMPS
HOOD MAY BE REQUIRED BY LOCAL
CODE ENFORCEMENT AND/OR IF USED
WITH SOLID FUELS. MUST SPECIFY LEFT/
RIGHT COMPONENT MOUNTING

NOTE ON ALL MODELS

ALL ROTISSERIE MODELS
ARE AVAILABLE WITH REAR
LOADING TRAYS AND/OR
PRODUCT. PLEASE CONTACT
US FOR PRICING.



MODEL WB-48

CAPACITY 45 CHICKENS
32,000 BTU MAIN RADIANTS
5-15,000 BTU INPUT FLICKER FLAME
115 VOLT, 20AMP DEDICATED OUTLET
FULL LOAD 5.7 AMPS
HOOD MAY BE REQUIRED BY LOCAL
CODE ENFORCEMENT AND/OR IF USED
WITH SOLID FUELS. MUST SPECIFY LEFT/
RIGHT COMPONENT MOUNTING

MODEL DS-60

CAPACITY 63 CHICKENS
40,000 BTU INPUT MAIN RADIANTS
5-15,000 BTU INPUT FLICKER FLAME
115 VOLT, 20AMP DEDICATED OUTLET
FULL LOAD 5.7 AMPS
HOOD MAY BE REQUIRED BY LOCAL
CODE ENFORCEMENT AND/OR IF USED
WITH SOLID FUELS. MUST SPECIFY LEFT/
RIGHT COMPONENT MOUNTING

MODEL BZ-72 DD

CAPACITY 72 CHICKENS
50,000 BTU INPUT MAIN RADIANTS
5-20,000 BTU INPUT FLICKER FLAME
115 VOLT, 20AMP DEDICATED OUTLET
FULL LOAD 5.7 AMPS (per cavity)
HOOD MAY BE REQUIRED BY LOCAL
CODE ENFORCEMENT AND/OR IF USED
WITH SOLID FUELS.

Date code: R2A © Remco US Patent: # 5,373,778-5,560,285-5,799,569-5,373,778 Canadian Patent # 2,172,586

Remco Renaissance Rotisserie Technical Specifications

RRS
034